

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, T24-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2769-70)

Set a basalt stone 12x10x10 ins., 8" in the ground for cor. of secs. 7, 12, 13 and 18 mkd. with 2 notches on N. and 4 notches on S. edges; from which

A Cedar 14" dia., bears N.38°E., 9 lks. dist. mkd. T24S R1E S7 BT.

A Cedar 36" dia., bears S.36°E., 25 lks. dist. mkd. T24S R1E S18 BT.

A Hemlock 14" dia., bears S.14°W., 10 lks. dist. mkd. T24S R1W S13 BT.

A Hemlock 14" dia., bears N.5°W., 42 lks. dist. mkd. T24S R1W S12 BT.

Cor. is on left bank of McKinley Creek, 350 ft. below top of spur.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 11, 1967 - C.S. File 52/42-57

Found - 16"x12"x12" corner stone mkd. with 2 notches on N. and 4 notches on S.

Orig. 14" now 17" Cedar snag, N.38°E., 5.9 ft. scribe "S R E S7" visible on unhealed blaze.

Orig. 36" now 42" Cedar, alive, S.36°E., 16.5 ft., blaze unhealed, face decayed, no scribe.

No trace of orig. NW. and SW. BTs.

Since a new logging access road will be constructed through this corner locus, we run West 75.0 ft. and Set Witness Corner. Set brass cap at W.C. mkd. Douglas Co. Surveyor

Office 1967

T 24 S R 1 W

Wit. Cor. 75' E. to Cor

S 12 | S 7

S 13 | S 18

New BTs- 10" Hemlock N.54°W., 19.3 ft. mkd. W.C. T24S R1W S12 DCS BT.

10" Hemlock S.37°W., 18.1 ft. mkd. W.C. T24S R1W S13 DCS BT.

The Wit. Cor. is for Douglas-Lane County Line, 30 ft. West of Francis Creek, course SE.

Fd. OK, DCSO by V. Tracy - Sept. 1969- C.S. File 52/42-62A

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, T24-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Lane County Surveyor's Office - Mikeal Blomme - Crew: Bruce Bothel & Stuart Duce - may 1, 2015 (Added to DCSO records 6/21/2020) - C.S. File 65/106-026

This cor. is on left bank of McKinley Creek
Since a new logging access road will be constructed through this corner locus, we run West 75.0 ft. and Set Witness Corner.

Found - At the corner position found a 12"x12"x16" basalt stone with 2 notches facing skyward, 4 notches facing south. the stone was found lying on the surface, beneath a 32" log, which appears to have rolled the stone out of its original position, (per the W.C.) By 1.7'.

Set - At a point east, 75 0' of the W.C., set a 1" x 30" iron pipe with a 2³/₈" brass cap to mark the section corner. Set a blue "DEEP-1" magnet below the pipe. buried the stone on the west side of the pipe the cap was set 6" above ground in a stone mound. No evidence of a logging road at the corner point was found.

Found - W.C., 1" I. Post W/2¹/₂" brass cap "D.C.S.O.-1967" WEST, 75.00'
1896, 47" Cedar leans to south S.32°10'E., 15.1' to approx. ctr

1967, 12" Hemlock W/scar N.54°20'W., 19.7' to ctr
New - Set 5/8"x30" rebar W/2" alum. cap "LCSO-RP1-2015", 4" below surface N.6°12'E., 71.75'
Set 5/8"x30" rebar W/2" alum. cap "LCSO-RP2-2015" 4" below surface S.87°42'E., 37.64'

Note- BT Distance shown is to an aluminum nail set at side/center of live trees.
Basis of bearing: True bearings, based on a solar observation using the hour-angle method.
Geographic map location: For finding the corner area - not of survey grade accuracy nad 83/91 values:
Lat: N 43°29'42.6" Long: W 122°44'29.8"