

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2769)

-----  
Set a basalt stone 24x16x10 ins., 18" in the ground for ¼ sec. cor. mkd. ¼ on W. face; from which  
A Fir 30" dia., bears S.70°E., 15 lks. dist. mkd. ¼ S BT  
A Fir 20" dia., bears S.64°W., 68 lks. dist. mkd. ¼ S BT.  
Cor. is on a steep hillside, sloping E.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - July 2, 1986 - C.S. File 62/37-3

-----  
Found - A 24" x 16" x 10" basalt stone mkd. "¼" on W. face. Stone is tipped out of position 1.5 ft. No. (Orig.)  
30" now 30" dia. D.Fir snag with a single fully healed blaze, bears S.70°E., 9.9 ft. (agrees w/rec.)  
20" now 24" dia. 1 ft. high rooted D.Fir stump, no blaze or scribing found, bears S.64°W., 43.9 ft. (Rec. S.64°W., 44.9 ft. is a slope measurement.)  
Orig. plumb position of orig. stone referenced, stone is removed and a 2 3/8" brass cap on a 1¼" x 32" I.P. is SET in its place protruding 1" above a 2 ft. dia. 1 ft. tall mound of stone set along South edge of I.P. with "¼" mark facing West. Cap mkd. "Douglas County Surveyors T24S ¼ R1W S12 S7 R1E 1986 Office."  
New BTs- 8" D.Fir double blazed and scribed "¼ S7 CS BT" bears N.69°E., 14.8 ft.  
4" I.Cedar double blazed and scribed "X BT" bears S.22½°E., 7.0 ft.  
11" D.Fir double blazed and scribed "¼ S12 CS BT" bears S.45½°W., 32.5 ft.  
11" D.Fir double blazed and scribed "¼ S12 CS BT" bears N.09¼°W., 9.0 ft.  
Corner lies approx. 250 ft. N. of the NW. corner of a new steep westerly facing clear cut approx. 2 miles along USFS Rd. 2300-600.