

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2768)

Sete a basalt stone 16x10x8 ins., 12" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on the N. and 5 notches on S. edges; from which

A Fir 24" dia., bears N.8°E., 109 lks. dist. mkd. T24S R1E S6 BT.

A Fir 12" dia., bears S.18°E., 35 lks. dist. mkd. T24S R1E S7 BT.

A Fir 36" dia., bears S.59°W., 55 lks. dist. mkd. T24S R1W S12 BT.

A Fir 36" dia., bears N.10°W., 54 lks. dist. mkd. T24S R1W S1 BT.

Cor. is on a steep hillside, sloping SE.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept. 4, 1969 - C.S. File 52/42-62

Found - Orig. Corner stone 16x10x8 ins., mkd. with 1 notch on N. and 5 notches on S. sides, in place.

Orig. 12" now 20" Fir, alive, S.18°E., 23.1 ft., very good scar.

Orig. 36", 40" Fir, alive, S.59°W., 36.3 ft., very good scar.

Orig. 36" now 40" Fir, alive, N.10°W., 35.6 ft., very good scar.

Orig. BT, to SE. gone.

Set Brass cap at cor. mkd: County Surveyors Office

R T 24 S R

1 S 1 | S 6 1

W S 12 | S 7 E

1969

New BT - 10" D.Fir N.41°E., 36.8 ft. mkd. T24S R1E S6 DCS BT. Corner lies 80 ft. N. of small creek, course SW.