

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2767)

-----

Set a basalt stone 20x12x6 ins., 15" in the ground, for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 12" dia., bears N.44°E., 75 lks. dist. mkd. ¼ S BT  
A Fir 30" dia., bears N.86°W., 73 lks. dist. mkd. ¼ S BT  
Cor. is on a steep hillside, sloping West.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Sept. 1969 - C.S. File 54/42-63

-----

Found - Basalt corner stone, as called for, in place, mkd. "¼" on W. face.  
Orig. 12" now 22" Fir, alive, N.44°E., 49.5 ft. shows good scars.  
Orig. 30" now 36" Fir, alive, N.86°W., 48.2 ft., shows good scars.  
Set Brass cap at cor. mkd: County Surveyors Office 1969  
(Reset stone alongside) T24S R1W ¼ S1|S6 R1E  
New BTs- 14" D.Fir N.15°E., 9.4 ft. mkd. "¼ S6 DCS BT".  
12" D.Fir S.45°W., 10.0 ft. mkd. "¼ S1 DCS BT"  
Corner lies on very steep, West slope, 75 ft. N. of top of spur.