

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 7 Page(s) 2947)

-----

Set  $\frac{1}{4}$  sec. post, from which  
A Fir 40" dia., bears S.80°E., 32 lks. dist.  
A Fir 40" dia., bears S.40°W., 12 lks. dist.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadstral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13287)

-----

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, determined at record distance from the original bearing trees:

A Fir 46" dia., bears N.74°E., 32 lks. dist. mkd.  $\frac{1}{4}$  S on bark. I reblaze and remark " $\frac{1}{4}$  S31 BT". (Rec. brg. S.80°E.)

A Fir 48" dia., bears S.23 $\frac{1}{4}$ °W., 12 lks. dist., blaze burnt. I reblaze and remark  $\frac{1}{4}$  S36 BT. (Rec. brg. S.40°W.)

At the corner point

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd:

$\frac{1}{4}$   
S 36 S 31  
1951