

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T24-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 7 Page 2947)

-----  
 Set post cor. to secs. 25, 30, 31 and 36, from which  
 A Hemlock 24" dia., bears N.60°E., 24 lks. dist.  
 A Hemlock 18" dia., bears S.25°E., 10 lks. dist.  
 A Hemlock 14" dia., bears S.25°W., 14 lks. dist.  
 A Spruce 30" dia., bears N.72°W., (?) dist.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13287-88)

-----  
 The Sec. Cor. determined at record distance from the old SE. and SW. bearing trees:

- A Hemlock stub 18" dia., bears S.26°45'E., 10 lks. dist., blaze healed. (Rec. brg. S.25°E.)
- A fallen Hemlock 18" dia., bears S.41½°W., 24 lks. dist., edge of face of old blaze under 78 years overgrowth. (Rec. brg. S.25°W.)
- A dead Fir 22" dia., bears N.63¼°W., 22 lks. dist., with partial scribe marks on old bark blaze. (Rec. a Spruce, 30" dia., bears N.72°W., no dist. given.)

At the corner point

Set an iron post, 36" long, 2" dia., 22" in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd:

T 24 S	
R 3 W	R 2 W
S 25	S 30
S 36	S 31
1951	

from which

- A Fir 24" dia., bears N.82°E., 72 lks. dist. mkd. T24S R2W S30 BT.
- A Fir 24" dia., bears S.26½°E., 143 lks. dist. mkd. T24S R2W S31 BT.
- A sawed Fir stump 32" dia., bears S.50½°W., 52 lks. dist. mkd. T24S R3W S36 BT.
- A Fir 22" dia., bears N.41¼°W., 23 lks. dist. mkd. T24S R3W S25 BT.

Weyerhaeuser Co. - Date of survey Sept. 1955 - Filed with DCSO July 1960 - C.S. File 42/323

-----  
 Found evidence of the original GLO corner, but did not reference.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - Brant Miller, Party Chief - Eric Sprinkle,  
Witness - 6/1/2012 - C.S. File 65/76-59

-----  
Found - 1951 BLM brass capped iron pipe in mound of stones.  
35" dia., fir stump bears N.82°E., 47.5 ft.  
34" dia., fir stump bears S.26½°E., 94.4 ft.  
The fir N.41¼°W., 15.2 ft. is a windfall.  
New - 9" dia., Fir bears N.37°E., 14.5 ft. scribed "T24S  
R2W S30 BT"  
An 8" dia., Hemlock bears S.82°E., 22.9 ft. scribed  
"T24S R2W S31 BT"  
An 11" dia., Cedar bears S.25°W., 9.5 ft. scribed  
"T24S R3W S36 BT"  
A 6 ft. steel post is set 2 ft. west.  
Note - Dec. 18°E