

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T24-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 - (DCSO records Vol. 7 Page(s) 2962)

-
- Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 7 and 12, marked T24S S6 on NE.; R2W S7 on SE.; R3W S12 on SW. and S1 on NW. faces with 1 notch on N. and 5 notches on S. edges, from which
- A Maple 7" dia., bears N.71°E., 20 lks. dist. mkd. T24S R2W S6 BT.
 - A Yew 12" dia., bears S.55°E., 70 lks. dist. mkd. T24S R2W S7 BT.
 - A Hemlock 24" dia., bears S.25°W., 31 lks. dist. mkd. T24S R3W S12 BT.
 - A Yew 18" dia., bears N.60°W., 13 lks. dist. mkd. T24S R3W S1 BT.

Cor. Tied and used in GLO resurvey by Henry L. Chandler, Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2936-37)

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell; Randy Smith, crew - Dec. 16, 1982 - C.S. 62/1-36

-
- Found - Orig. 24" Hemlock now 28", 7 ft. high stump with scribed T24S R3W S12 BT visible in previously opened blaze.
- 40" Fir stump with "W" nail in face per Weyerhaeuser Co. unrecorded renewal. (Notes attached to this CS File)
- Set 1" x 30" Iron pipe with brass cap attached at record bearing and distance (N.25°E., 20.5 ft.) from original Hemlock BT. Cap mkd. "Douglas Co. Surveyor T24S R3W S1 S12 S6 S7 R2W 1982".
- New BTs-
- 40" Fir stump bears N.24°W., 47.6 ft. to "W" nail on face.
 - 6" Hemlock scribed "S12 CS BT" in double blaze bears S.2°E., 11.4 ft.
 - 11" Hemlock scribed "S6 CS BT" in double blaze bears N.25°E., 47.7 ft.
 - 5" Chinquapin scribed "S7 CS BT" in double blaze bears S.74°E., 25.0 ft.
- DCSO BT tags on all trees. End of road 711 and line crossing tag bears N.20°E., approx. 600 ft. from corner.