

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	Description

GLO survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2881)

Set hemlock post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 on N face, from which:
A fir, 18" dia., bears S.25°E., 32 lks., mkd: 1/4 S BT.
A hemlock, 20" dia., bears N.21°W., 15 lks., mkd: 1/4 S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13304)

Point for the 1/4 sec. cor. of secs. 30 & 31, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36" long, 1" dia., 18" in the ground, to solid rock & in a mound of stone, 4 ft. base to top, with brass cap marked:
$$\frac{1}{4} \frac{S \ 30}{S \ 31}$$

from which
A fir, 36" dia., bears N.34 1/2°E., 103 lks., mkd: 1/4 S30 BT.
A fir, 40" dia., bears N.26°W., 131 lks., mkd: 1/4 S30 BT.

Glen McChesney, Weyerhaeuser - 11/19/1969 - C.S. 53/110-16

Found - 1951 Brass cap.
36" now 40" Fir, bears N.35°E., 69.0 ft., scribing visible on single face. Dist. to center of BT.
40" now 42" Fir windfall, slid about 15' to north scribing visible on single face. Bearing & dist. to root hole N.26°W., 86.5 ft.
New - Added "W" nail & plate to 40" Fir, N.35°E., 67.8 ft.
26" Cedar snag, N.45°W., 66.4 ft., "W" nail & plat.

Ron Rice, NW Land Surveying - Jason Collier - Sept. 6, 2012 - C.S. File 65/77-34

Found - 1" dia. Iron post with BLM brass cap dated 1951
36" now 40" Fir, bears N.35°E., 69.0 ft., scribing visible on single face. Dist. to center of BT. (Fd 32" dia x6' high stump with scribing visible)
40" now 42" Fir windfall, slid about 15' to north scribing visible on single face. Bearing & dist. to root hole N.26°W., 86.5 ft. (Not found)
26" Cedar snag, N.45°W., 66.4 ft., "W" with nail and plate (Found 26" dia. x 5' high Cedar stump tag)
New - 13" D. Fir bears N.18°E., 5.8 ft., scribed 1/4 S30 BT
continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - 12" D. Fir bears S.87°W., 13.3 ft., scribed ¼ S31 BT
16" D. Fir bears S.65°E., 39.9 ft., scribed ¼ S31 BT
Corner has steel post adjacent to it. All BTs have
orange painted bands and yellow tags.
Decl. 16 East