

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 31, T23-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2176-77)

Set Dogwood post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on N. face, from which
A Maple 5" dia., bears N.12°W., 21 lks. dist. mkd. ¼ S BT
A Maple 6" dia., bears S.60°W., 15 lks. dist. mkd. ¼ S BT

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2184)

(39.60 chs.)
Old ¼ sec. cor., a post bears South 3.00 chs. dist. I destroyed this post and the markings on old bearing trees. (40.00 chs. West)
Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Hemlock 7" dia., bears S.30°W., 13 lks. dist. mkd. ¼ S BT.
A Vine Maple 6" dia., bears N.66°W., 33 lks. dist., mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 11, 1969 - C.S. File 54/27-107

Found 1/2" Monel pipe and 1½" x 8 ft. mkd. pipe. No trace original BTs.
Weyerhaeuser method BTs:
60" Fir stump S.81°W., 3.9 ft. "W" nail and tag.
54" Fir stump N.37°E., 16.0 ft. "W" nail and tag.