

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2871-72)

-----  
Set Cedar post 4" sq., 4 ft. long, 24" in the ground for cor. to secs. 5, 6, 31 and 32, mkd. T24S S32 on NE.; R2W S5 on SE.; T25S S6 on SW.; S31 on NW. faces, with 1 notch on W. and 5 notches on E. edges, from which  
A Fir 48" dia., bears N.20°E., 50 lks. dist. mkd. T24S R2W S32 BT.  
A Hemlock 18" dia., bears S.85°E., 78 lks. dist. mkd. T25S R2W S5 BT.  
A Fir 40" dia., bears S.50°W., 20 lks. dist. mkd. T25S R2W S6 BT.  
A Hemlock 10" dia., bears N.60°W., 50 lks. dist. mkd. T24S R2W S31 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13282-83)

-----  
"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 having proved to be fictitious, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon." (Hezekiah Johnson fictitious corner on Page 3656)

The cor. of secs. 31 and 32, determined from the original bearing trees:

- A Fir 50" dia., bears N.25°E., 50 lks. dist., with partial scribe marks on old bark blaze. (In 1951) (Rec. brg. N.20°E.) In 1963, this is a sawed Fir stump with no marks remaining.
- A Hemlock 20" dia., bears N.85°E., 70 lks. dist., mkd. T25 R2 S5 BT. (Rec. S.85°E., 78 lks. dist.)
- A Fir 50" dia., bears S.55°45'W., 20 lks. dist., with partial scribe marks on old bark blaze. (Rec. brg. S.50°W.)
- A broken Hemlock 14" dia., bears N.56°W., 50 lks. dist. mkd. T24 R2 S31 BT. (Rec. brg. N.60°W.)

At the corner point  
(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T25-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set an iron post 36" long, 2" dia., 20" in the ground to solid rock and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 24 S | R 2 W  
S 31 | S 32  
S 6 | S 5  
T 25 S  
1951

from which new bearing trees:

- A Hemlock 9" dia., bears S.68°E., 91 lks. dist., mkd. T25S R2W S5 BT. (1963 BT)
- A Yew 7" dia., bears S.86½°W., 40 lks. dist. mkd. T25S R2W S6 BT. (1963 BT)
- A Hemlock 16" dia., bears N.12¼°W., 85 lks. dist., mkd. T24S R2W S31 BT. (1951 BT)

Fd BC & 7 BTs B Shaner, 6/1964 CS 51/281-2 (added 10/16/2018)

David Edwards - March 2013 - C.S. File 65/78-12

- 
- Found - 1951 BLM brass cap in mound of stones.  
The original bearing trees are all stumps.  
The 1951 Yew BT is down.  
A 19" dia. Hemlock with healed blaze bears S.68°E., 60.1 ft.  
A 27" dia. Hemlock with healed blaze bears N.12¼°W., 56.1 ft.  
Both are 1951 BLM bearing trees.
- New - An 8" dia. Fir scribed "T24S R2W S32 BT" bears N.72°E., 35.8 ft.  
A 9" dia. Fir scribed "T25S R2W S6 BT" bears S.22°N., 32.0 ft.  
A 6 foot steel post is set 2.5 ft N.85°E.
- Note - Decl. 18 East.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749, surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23330-1)

- 
- The cor. of secs. 5, 6, 31, & 32, on the N. bdy. of the Tp., perpetuated by Edwards, in 2013, monumented with an iron post, 2" dia., firmly set, projecting 5" above the ground, in a collar of stone, with a brass cap (properly) mkd.  
from which the remains of the original bearing trees
- A decayed fir stump, 48" dia., bears N.25°E., 33.0 ft., with fragmentary scribe marks visible on a partially healed, decayed blaze.
  - A decayed hemlock stump, size indeterminate, bears N.85°E., 46.2 ft., with no marks visible. cont.

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, 52" dia., bears S.55¾°W., 13.2 ft., with no marks visible.  
and bearing trees mkd. by Tallett and White in 1951-63  
A hemlock, 18" dia., bears S.68°E., 60.1 ft., with a healed blaze.  
A hemlock, 27" dia., bears N.12¼°W., 56.1 ft., with a healed blaze.  
and bearing trees mkd. by Edwards  
A D.Fir, 10" dia., bears N.71°E., 36.3 ft., with scribe marks T24S R2W S32 visible on a partially healed upper blaze and BT visible in lower blaze.  
A D.Fir, 11" dia., bears S.22¾°W., 31.3 ft., with scribe marks T25S R2W S6 visible on a partially healed upper blaze and BT visible in lower blaze.  
From this cor., a point established by person(s) unknown, monumented with an iron pipe, 2" dia., firmly set, projecting 4" above the ground, bears N.22°56'49"W., 4.00 ft., and is not utilized in the course of this survey

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/6/2023 - C.S. File 67/56-64  
-----  
Found - BLM 2½" brass cap (properly mkd) in mound of stone up 5".  
Orig BTs-Burned 48'x2½ ft, decayed Fir stump, N.25°E. 33.1 ft 3"x3 ft. fir stump S.55¾°W., 13.2 ft.  
BTs by Tallett & White -  
    Burnt, dead 18" hemlock S.68°E., 60.1 ft., healed blaze, 3½" mag nail, right side center.  
    Burnt, sawn 28"x2 ft. hemlock stump N.12¼°W., 56.1 ft. healed blaze, 3½" mag nail, right side center  
BTs by Edwards -  
    Burned-dead 13" hemlock S.21°W., 31.3 ft. (rec. S.22¾°W.) burned out blaze, 3½" mag nail, right side center.  
New - Burned-dead 21" hemlock S.23°E., 17.8 ft., 3½" mag nail, right side center.  
    Burned-dead 12" hemlock S.14°W., 23.0 ft., 3½" mag nail, right side center.  
Note: Trees not blazed or scribed.  
Note - Area burnt 9/2020  
    Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 218250.752      E 260567.307