

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2879)

Set fir post, 3 ft. long, & 3" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S on W face, from which:

A fir, 30" dia., bears N.75°W., 61 lks., mkd: 1/4 S BT.

A hemlock, 12" dia., bears S.65°E., 55 lks., mkd: 1/4 S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13301-2)

Point for the 1/4 sec. cor. of secs. 31 & 32, determined at rec. bearing & distance from the orig. SE BT.

A dead hemlock, 18" dia., bears S.65°E., 55 lks., scribe marks 1/4 S visible in partially healed upper blaze, the lower blaze healed.

Set an iron post, 36" long, 1" dia., 20" in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap marked:

1/4
S 31|S 32
1951

from which

A fir, 28" dia., bears N.71 1/2°E., 85 lks., mkd: 1/4 S32 BT.

A fir, 32" dia., bears S.77 1/2°W., 54 lks., mkd: 1/4 S31 BT.