

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2880)

-----  
Set a cedar post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 29, 30, 31, & 32, marked T24S S29 on NE, R2W S32 on SE, S31 on SW, S30 on NW faces, with 1 notch on S & 5 notches on E edges; from which  
A fir, 36" dia., bears N.55°E., 114 lks., mkd: T24S R2W S29 BT.  
A fir, 30" dia. bears S.30°E. 65 lks. mkd: T24S R2W S32 BT  
A fir, 40" dia. bears S.83°W. 65 lks. mkd: T24S R2W S31 BT  
A fir, 36" dia. bears N.15°W. 63 lks. mkd: T24S R2W S30 BT

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13302-3)

-----  
The cor. of secs. 29, 30, 31, & 32, determined at rec. dist. from the orig. BTs:  
A fir, 42" dia., bears N.59°E., 114 lks., with partial scribe marks on old bark blaze, breast high. I reblaze & remark T24S R2W S29 BT. (Rec. bearing N.55°E.)  
A fir, dead & fallen, 30" dia., bears S.50°E., 65 lks., with partial scribe marks on old bark blaze. (Rec. bearing S.30°E.)  
A fir, 44" dia., bears S.77°W., 65 lks., with partial scribe marks on old bark blaze, breast high. I reblaze & remark, T24S R2W S31 BT. (Rec. bearing S.83°W.)  
A fir, 46" dia., bears N.8°W., 63 lks., blaze healed. (Rec. bearing N.15°W.)

At the corner point  
Set an iron post, 36" long, 2" dia., 28" in the ground, with brass cap marked:

T24S	R2W
S 30	S 29
S 31	S 32
1951	

from which  
A fir, 48" dia. bears S.74°E. 25 lks. mkd: T24S R2W S32 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1969 - C.S. File 54/27-252

-----  
Found - 1951 Cad. brass cap in place as determined from remaining BT.  
48" Fir sawed stump, S.74°E., 16.5 ft., fragmentary scribe on burned blaze. Rescribed "T24S R2WS32CS BT"  
continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 16" Hemlock S.21°W. 105.2 ft. mkd: T24S R2W S31 CSBT  
Found - Weyerhaeuser BT: 48" Fir stump S.77°W., 42.9 ft.  
This also Orig. BT, no scribe fd, badly burned.  
This corner lies on bench in dense fir reproduction,  
greasewood & vine maple brush.

Ron Rice, NW Land Surveying - Jason Collier - Sept. 6, 2012 -  
C.S. File 65/77-36  
-----  
Found - 2" dia. Iron post with BLM brass cap dated 1951  
48" Fir sawed stump, S.74°E., 16.5 ft., fragmentary  
scribe on burned blaze. Rescribed "T24S R2W S32  
CS BT" (Found with no marks)  
16" Hemlock S.21°W., 105.2 ft. mkd: T24S R2W S31 CS  
BT (Fd 32" Hemlock with healed face)  
Weyerhaeuser BT: 48" Fir stump S.77°W., 42.9 ft. (Fd  
in same condition)  
New - 20" D.Fir bears S.32°E., 6.9 ft scribed T24S R2W S32 BT  
19" D.Fir bears N.72°E. 28.1 ft scribed T24S R2W S29 BT  
23" D.Fir bears N.6°E., 33.6 ft scribed T24S R2W S29 BT  
Note - Corner has steel post adjacent to it. All BTs have  
orange painted bands and yellow tags.  
Declination 16° East

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 10/25/2022 - C.S. File 67/54-28  
-----  
Found - 2½" Brass cap on 2" Iron pipe up 14".  
Burned 46"x4 ft sawn fir stump S.74°E., 16.5 ft.  
scar burnt off. BLM  
Burned-sawn 22"x6 ft. D.Fir stump S.33°E., (rec.  
S.32°E.) 6.9 ft. Rice  
Burned-sawn 21"x6 ft. D.Fir stump N.70½°E., (rec.  
N.72°E.) 28.1 ft. healed blaze, scar burnt. Rice  
Burned-sawn 25"x7 ft. D.Fir stump N.3½°E., 33.9 ft  
(rec N.6°E. 33.6 ft) healed blaze good scar. Rice  
Un-recorded 1¼" ID iron pipe N.8°E., 4.7 ft., up 15"  
All BTs have 3½" mag spikes - top center spiked if  
4' or less, right side center spiked otherwise  
Note - Area burnt 9/2020  
Compass decl. 14½°E.  
ORCS Co-ordinate reference system south zone  
Cottage Grove-Canyonville  
N 223346.965  
E 260649.714