

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GL0 survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2883)  
-----  
Set dogwood post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 on W face, from which:  
A hemlock, 10" dia., bears N.10°E., 13 lks., mkd: 1/4 S BT.  
A vine maple, 6" dia., bears S.30°W., 9 lks., mkd: 1/4 S BT.

Weyerhaeuser - 1958-1961-1964 - C.S. File 53/110-13  
-----  
Found - 3"x3' dogwood post, gone, 2"x2" fir pitch post set in 1955 from orig. BTs now gone.  
No trace 10" Hemlock N.10°E., 8.6 ft.  
No trace 6" Vine Maple S.30°W., 5.9 ft.  
1955 W.Co BTs -  
46" Fir N.22°E., 22.1 ft., now stump "W" nail OK plate gone.  
60" Fir S.79°W., 28.0 ft., now stump "W" nail & plate OK.  
50" Fir N.23°W., 32.9 ft., now stump "W" nail & plate OK.  
52" Fir S.12°E., 17.3 ft., now stump "W" ok plate replaced.  
Set - 5/8"x32" monel pipe, 1 1/2"x10' yellow pipe for marker driven alongside monel pipe.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 10/19/2023 - C.S. File 67/57-6  
-----  
Found - 5/8" monel pipe below surface, top 10" bent southerly, bottom still plumb.  
Rotted, sawn, 40"x2 1/2 ft. Fir, N.22°E., 22.1 ft. "W" nail gone.  
60" sawn Fir stump, S.79°W., 28.0 ft. "W" nail and BT tag on ground NE edge of stump  
Rotted 55"x1 ft. fir stump N.23°W., 32.9 ft.  
51"x1 1/2 ft. fir stump S.12°E., 17.3 ft.  
4 1/2 ft. remnant of 1 1/2"x10 ft. yellow pipe is found on top of ground approx. 70 ft. southerly of monel pipe.  
New - 3 3/4" alum cap with magnet core on 2 1/2" O.D. x 28" alum. pipe. Reference monel pipe location. BT bearing and dist. check good with record. Cap set below surface, monel pipe on west edge of cap up 8". Cap mkd:  
continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DOUGLAS COUNTY  
SURVEYORS OFFICE  
T24S R2W  
¼ S19 |  
          | S20  
          |  
          2023

Set 5/8"x30" iron rods with DCS0 plastic caps up 4"  
N.26°E., 8.1 ft.                   S.53°E., 9.8 ft.  
S.19½°W., 8.8 ft.               N.39°W., 8.6 ft.

Note - Area bunt 9/2020  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 231298.437           E 260613.831