

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2883-4)

Set a yew post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 17, 18, 19, & 20, marked T24S S17 on NE, R2W S20 on SE, S19 on SW, S18 on NW faces, with 3 notches on S & 5 notches on E edges; from which
A fir, 12" dia. bears N.50°E. 17 lks. mkd: T24S R2W S17 BT
A fir, 10" dia. bears S.40°E. 35 lks. mkd: T24S R2W S20 BT
A fir, 18" dia. bears S.35°W. 55 lks. mkd: T24S R2W S19 BT
A fir, 36" dia. bears N.5°W., 15 lks. mkd: T24S R2W S18 BT

Glen McChesney, Weyerhaeuser Co. - Jan 21 1980 - C.S. 58/8-22

Found - No trace of 1883 Yew post.
Orig. 12" now 30" Fir, healed over faces, bears N.60°E., 11.2 ft., (Rec. N.50°E.)
Orig. 10" now 18" Fir, healed over faces bears S.5°E. 23.1 ft., face measurement. (Rec. S.40°E.)
Orig. 18" now 26" down Fir, rooted. Axe work & 1 scribe mark, bears S.56°W., 36.3 ft., to root hole (rec. S.35°W)
Orig. 36" now 38" Fir stump, rotted but evidence of old face bears N.3°W., 9.9 ft., face measurement. (Rec. N.5°W.)
Bearing & distances are to a 1"x30" monel pipe set by GLO*
Accessories added this date:
30" Fir, N.59°E., 10.5 ft., (1883 BT) with "W" nail & plate.
38" Fir, S.86°E., 29.8 ft., with "W" nail & plate.
18" Fir, S.6°E., 23.0 ft., (1883 BT) with "W" nail & plate.
12" Yew, N.80°W., 18.6 ft., with "W" nail & plate.
* Could not find any rec. of a GLO resurvey.