

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2930)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 7, 8, 17, & 18, marked T24S S8 on NE, R2W S17 on SE, S18 on SW, S7 on NW faces, with 4 notches on S & 5 notches on E edges; from which
A hemlock, 8" dia., bears N.76°E., 37 lks., mkd: T24S R2W S8 BT.
A hemlock, 6" dia., bears S.70°E., 21 lks., mkd: T24S R2W S17 BT.
A cedar, 6" dia., bears S.41°30'W., 17 lks., mkd: T24S R2W S18 BT.
A cedar, 24" dia., bears N.39°W., 41 lks., mkd: T24S R2W S7 BT.

Charles Volz, Weyerhaeuser Co. - 11/25/1968 - C.S. 53/110-17

Found - Orig. 8" hemlock, now down & rotted, no scribing, root wad & rotted tree remains. Root wad hole bears N.65°E., 24.4 ft. (Rec. N.76°E.)
Orig. 6" hemlock, visible scribing, bears S.70°E., 13.4 ft. to scribing.
Orig. 6" now 12" cedar, standing - face no visible scribing - bears S.42°W., 10.4 ft. (Has Douglas appraisal tag)
Orig. 24" now 30" cedar, old face - no scribing visible, bears N.39°W., 25.6 ft. to face.
New - 30" Cedar (OBT) bears N.42°W., 24.1 ft., added "W" nail & plate.
60" Fir bears S.81°W., 20.3 ft., "W" nail & plate.
30" Cedar bears S.10°E., 42.0 ft., "W" nail & plate.
40" Cedar bears N.85½°E., 68.3 ft., "W" nail & plate