

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2933)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 5, 6, 7, & 8, marked T24S S5 on NE, R2W S8 on SE, S7 on SW, S6 on NW faces, with 5 notches on S & E edges; from which

- A fir, 10" dia., bears N.27°30'E., 53 lks., mkd: T24S R2W S5 BT.
- A hemlock, 20" dia., bears S.66°E., 46 lks., mkd: T24S R2W S8 BT.
- A fir, 30" dia., bears S.39°W., 42 lks., mkd: T24S R2W S7 BT.
- A fir, 36" dia., bears N.19°30'W., 53 lks., mkd: T24S R2W S6 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Aug 1969 - C.S. File 54/27-248

-----

Found - Unrecorded ½" monel pipe for corner & a 1½"x10' high marked pipe set from 3 OBTs. (Weyerhaeuser Cor.)

- Orig. 10" now 14" fir sawed stump, N.27½°E., 35.0 ft
- Orig. 10" now 32" fir sawed stump, S.39°W., 27.7 ft. good scar.
- Orig. 36" now 40" fir sawed stump, N.58°W., 35.0 ft. scribe reverse fd. Rec. bearing N.19½°W.

No trace of OBT to SE.