TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs. Vol. 7 Page(s) 2888-9)

Set fir post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ on N face, from which:
A cedar, 10" dia., bears N.10°W., 38 lks., mkd: ¼ S BT.
A cedar, 10" dia., bears S.40°W., 9 lks., mkd: ¼ S BT.

Glen McChesney, Weyerhaeuser - 5/25/1976 - C.S. File 59/46-76

Found - 10" now 14" Red Cedar, face healed over, bears N.7°W., 25.1 ft., center of tree measurement.
10" now 14" Red Cedar, scribing visible on unhealed face, bears S.23°W., 5.9 ft., (rec. S.40°W.) center of tree measurement.
Set - 1/2" iron pipe set by distance from BTs
Added "W" nail & plate to OBTs
48" Fir, S.2°W., 10. ft., "W" nail & plate.
40" Fir, N.23°W., 43.5 ft., "W" nail & plate.

Douglas Co. Surveyors Office - Rod Kimberling - P.L. Earle - March 15, 1978 - C.S. File 59/46-76

Found - 1/2" iron pipe, the top 3" above ground in a 24" mound of stones. I use as a bearing object
10" now 16" Cedar bears N.7½°W., (Rec. N.10°W.) 25.1 ft., with a well healed blaze & "B" carved on west face.
10" now 13" Cedar bears S.31°W., (rec. S.40°W.) 5.9 ft. with very old scribing "¼ S" in dead section of tree (east side of tree is dead)
Set - 1"x36" IP with a brass cap set at ground level in a dug pit 24" dia., 24" deep filled with stone. I mark brass cap: Douglas County Surveyor

$$\frac{¼}{\frac{S\ 20}{S\ 29}}$$
1978

New - 1/2" fd. iron pipe bears N.53°W., 0.6 ft.
Note - Corner is 200 ft., SW of North edge of virgin timber & small creek which bears N.20°W., slope is 72% N.40°E.