

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2925)

Set a basalt stone 15x12x6" 10" in the ground for ¼ sec. cor. marked ¼ on N face, from which
A fir, 36" dia., bears N.20°W., 11 lks., mkd: ¼ S BT.
A fir, 30" dia., bears S.50°W., 11 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Gary Langlitz - A. Victor Cangie - D. Stewart - April 26, 1976 - C.S. File 59/8-23

Found - 15"x12"x6" basalt stone with "¼" chiseled on north face, from which:
Orig. 36" now 42" D.Fir bears N.20°W., 7.3 ft. A scribed "S" is visible on partly opened blaze. Tree is dead.
Orig. 30" now 42" D.Fir bears S.50°W., 7.3 ft. Tree has healed over blaze & is alive & well.
Set - 1"x30" iron pipe with brass cap stamped:
Douglas County Surveyors
T24S R2W
¼ S 17
S 20
1976
New BT - 25" D.Fir bears S.29°E., 24.1 ft., mkd: "¼ S20 CS BT" in a double blaze.
Note - We replace orig. stone on north side of bras cap. Compass dec. 20° East.