

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John. A. McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO records Vol. 7 Page(s) 2886

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:

- A hemlock, 18" dia., bears N.20°W., 18 lks., mkd: ¼ S BT.
- A hemlock, 30" dia., bears S.27°E., 35 lks., mkd: ¼ S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13298-9)

Point for the ¼ sec. cor. of secs. 32 & 33, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36 long, 1" dia., 28" in the ground with brass cap marked:

¼
S 32 | S 33
1951

from which

- A Cedar, 13" dia., bears S.82¼°E., 43 lks., mkd: ¼ S33 BT. (1963 BT)
- A yew, 14" dia., bears N.56¼°W., 27 lks., mkd: ¼ S32 BT. (1951 BT, 16" dia., in 1963)

Ron Rice, NW Land Surveying - Jason Collver - Sept. 6, 2012 - C.S. File 65/77-33

Found - 1" dia. Iron post with BLM brass cap dated 1951

- A Cedar, 13" dia., bears S.82¼°E., 28.4 ft., mkd: ¼ S33 BT. (Fd 13" dia. x 5' high Cedar stump with scribing visible)
- A yew, 16" dia., bears N.56¼°W., 17.8 ft., mkd: ¼ S32 BT. (Fd 17" Yew with scribing visible)

New - 16" D.Fir bears N.76°W., 10.3 ft., scribed ¼ S32 BT
14" Hemlock bears N.68°E., 4.6 ft., scribed ¼ S33 BT
19" D.Fir bears S.20°E., 22.9 ft., scribed ¼ S33 BT

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Dec. 16°E

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 10/26/2022 - C.S. File 67/55-12

Found - 2½" BLM brass cap on 1" iron pipe reset, now up 8" Burnt out 10"x7' yew snag N.56¼°W., 17.8 ft. face gone. BLM Continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Burnt-dead 19" D.Fir N.76°W., 10.3 ft healed single blaze add 3½" mag nail right side center. Rice
Burnt-dead 16" hemlock N.68°E., 4.6' healed single blaze add 3½" mag nail right side center. Rice
Burnt-dead 22" D.Fir S.23°E. (Rec. S.20°E.) 22.9 ft. healed single blaze add 3½" mag nail right side center. Rice
New - Sawn-burnt 16"x2' fir stump S.26½°E., 84.3 ft. 3½" mag nail top center.
8"x6 ft. steel gate swing post (most northerly post) S.9¾°E., 122.5 ft.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Monument is on moderate NNE slope approx. 130' north of gravel road.
Lat: 43°26'17.82"N Long: 122°57'02.55"W.