

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John. A. McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs Vol. 7 Page 2886)

Set a cedar post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 28, 29, 32, & 33, marked T24S S28 on NE, R2W S33 on SE, S32 on SW, S29 on NW faces, with 1 notch on S & 4 notches on E edges; from which
A fir, 5" dia. bears N.70°E., 20 lks. mkd: T24S R2W S28 BT
A fir, 8" dia. bears S.20°W., 10 lks. mkd: T24S R2W S33 BT
A fir, 5" dia. bears S.60°W., 18 lks. mkd: T24S R2W S32 BT
A fir, 10" dia. bears N.15°W. 22 lks. mkd: T24S R2W S29 BT

Fd. & used on GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2913)

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13299)

Point for the cor. of secs. 28, 29, 32 & 33, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36" long, 2" dia., 24" in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap marked:
T24S R2W
S 29 | S 28
S 32 | S 33
1951
from which
A fir, 11" dia. bears N.46°E. 42 lks. mkd: T24S R2W S28 BT
A fir, 14" dia. bears S.19°E. 33 lks. mkd: T24S R2W S33 BT
A fir, 16" dia. bears S.75°W. 15 lks. mkd: T24S R2W S32 BT
A fir, 12" dia. bears N.7°W. 30 lks. mkd: T24S R2W S29 BT

FD. ok by Glenn McChesney, WEYCO, 4/8/1970 - C.S. File 53/110-15 - Added "W" nail & plate.

Ron Rice, NW Land Surveying - Jason Collver - Sept. 6, 2012 - C.S. File 65/77-37

Found - 2" dia. Iron post with BLM brass cap dated 1951
A fir, 11" dia. bears N.46°E., 42 lks. mkd: T24S R2W S28 BT (Fd 26" D. Fir with healed face)
A fir, 14" dia. bears S.19°E. 33 lks. mkd: T24S R2W S33 BT (Fd 18" D. Fir with healed face)
A fir, 16" dia. bears S.75°W. 15 lks. mkd: T24S R2W S32 BT (Fd 29" D. Fir with healed face) cont.

