

TOWNSHIP 24 RANGE 2 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION CORNER SEC 28, 29, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John. A. McQuinn, Deputy Surveyor, under Contract #466 dated April 1883 - (DCSO recs Vol. 7 Page 2888)

Set fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to secs. 20 & 21, 28 & 29 marked T 24 S S 21 on N.E., R2 W S 28 on S.E., S 29 on S.W. and S 20 on N.W. faces with 2 notches on S. and 4 notches on E. edges, from which:
 A fir, 24 ins. diam., bears N.45°E. 10 lks. dist. marked T 24 S R 2 W S 21 B T.
 A fir, 18 ins. diam., bears S.40°E. 30 lks. dist. marked T 24 S R 2 W S 28 B T.
 A fir, 18 ins. diam., bears S.15°W. 9 lks. dist. marked T 24 S R 2 W S 29 B T.
 A fir, 5 ins. diam., bears N.65°W. 20 lks. dist. marked T 24 S R 2 W S 20 B T.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 01/15/2026 - C.S. File 67/61-58

NOT FOUND.
Determined GPS search areas using corner ties from existing corners to North, East, and South. Checked stream calls North and East. Area that agrees with stream calls has no fir B.T. evidence.