

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2923)

Set a basalt stone 15x8x6", 10" in the ground for cor. to secs. 16, 17, 20, & 21, marked with 3 notches on S & 4 notches on E edges, from which
A fir, 36" dia. bears N.25°E. 30 lks. mkd: T24S R2W S16 BT
A fir, 40" dia. bears S.40°E. 12 lks. mkd: T24S R2W S21 BT
A fir, 15" dia. bears S.36°W. 70 lks. mkd: T24S R2W S20 BT
A fir, 24" dia. bears N.75°W. 31 lks. mkd: T24S R2W S17 BT

L. B. Wilson, Weyerhaeuser - 7/3/1970 - C.S. File 53/110-24

Found - Stone in place.
36" now 60" fir, face grown over, bears N.45°E., 19.6' (rec. N.25°E.) center of tree measurement.
40" now 48" fir snag, scribing visible, bears S.40°E., 7.9 ft. center of tree measurement.
15" now 18" fir, face healed over, bears S.36°W., 44.7 ft., center of tree measurement.
24" now 36" fir, face healed over, bears N.73°W., 20.8 ft., center of tree measurement.
New - Added "W" nail & plate to all OBTs.