

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2929)

Set a basalt stone 15x12x6" 10" in the ground for ¼ sec. cor. marked ¼ on N face, from which

- A hemlock, 18" dia., bears N.70°W., 29 lks., mkd: ¼ S BT.
- A fir, 20" dia., bears S.89°E., 39 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1969 - C.S. File 54/27-259

Found - 1½" I. Pipe for ¼ corner & 10' (?) high 1½" marker pipe set from OBTs as follows:

- Orig. 18" now 24" Hemlock, N.70°W., 19.1 ft., now stump - scribe marks visible "W" nail & tag.
- Orig. 20" now 26" Fir S.89°E., 25.7 ft., now stump - low cut "W" nail & tag.

Weyerhaeuser reference -

- 28" D.Fir stump S.8°W., 12.0 ft., "W" nail & tag.
- No new trees available, extremely dense Greasewood, willow brush & small fir & hemlock reproduction.