

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2926)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
A chinquapin, 6" dia., bears S.30°E., 43 lks., mkd: ¼ S BT
A fir, 48" dia., bears N.40°E., 12 lks., mkd: ¼ S BT.

Glenn McChesney, Weyerhaeuser Co - June 10, 1977 (filed 12/1980) - C.S. File 58/8-21

Found - Orig. 54" Fir, chopped open lower part of single face & exposed scribed "T" bears N.40°E., 7.9 ft. face measurement.
Orig. 6" Chinquapin, now 8"x4 ft., Chinquapin stub, remainder of old face, scribing no longer visible, S.30°E., 28.4 ft., face measure.
(Fir BT identified by John Fuchek, Weyerhaeuser in 1941)
New - 54" Fir, N.40°E., 7.5 ft., (orig. BT) with "W" nail & plate.
40" Fir, S.6½°W., 25.5 ft., with "W" nail & plate.