

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T25-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2869-70)

Set post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 3, 4, 33 and 34, marked T24S S34 on NE.; R2W S3 on SE.; T25S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges, from which

- A Fir 20" dia., bears N.19°E., 72 lks. dist. mkd. T24S R2W S34 BT.
- A Hemlock 30" dia., bears S.43°E., 22 lks. dist. mkd. T25S R2W S3 BT.
- A Fir 18" dia., bears S.43°W., 22 lks. dist. mkd. T25S R2W S4 BT.
- A Fir 30" dia., bears N.20°W., 18 lks. dist. mkd. T24S R2W S33 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13279-80)

"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon." (Hezekiah Johnson fictitious corner on Page 3626)

Point for the cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This now becomes the cor. of secs. 3, 4, 33 and 34. Set an iron post 36" long, 2" dia., 28" in the ground with brass cap mkd.

T 24 S R 2 W
S 33 S 3
 S 4 S 3
 1951

from which

- A Cedar 20" dia., bears N.40°E., 39 lks. dist. mkd. T24S R2W S34 BT. (1951 BT)
- A Hemlock 6" dia., bears S.32°E., 53 lks. dist. mkd. T25S R2W S3 BT. (1963 BT.)
- A Chinquapin 16" dia., bears S.64¼°W., 33 lks. dist. mkd. T25S R2W S4 BT. (1963 BT)

(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T25-2

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A Fir 26" dia., bears N.46½°W., 69 lks. dist. mkd. T24S
R2W S33 BT. (1951 BT)