

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400113

PRIMARY CORNER DESCRIPTION NW Cor. TR 38 (Sec. 34)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13295)

-----  
Point for the NW cor. of Tract No. 38, sec. 34.  
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T 24 S R 2 W  
S 33 | S 34  
| TR 38  
1963

from which

A fir, 30" dia., bears N.70°E., 77 lks., mkd: S34 BT.  
A cedar, 30" dia., bears S.6°W., 37 lks., mkd: TR38 S34 BT

Fd. 2 BTs & BC 3/1968 DCSO C.S. File 54/27-144

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 5/2015 - C.S. File 65/89-5

-----  
Found - BLM brass cap (properly mkd)  
43" D.Fir N.70°E., 50.0 ft (Rec. 50.8 ft) good scar.  
40" Cedar S.6°W., 27.7 ft. (Rec. 24.4 ft) good scar.  
New - 9" Fir N.36°E., 36.3 ft. scribed T24S R2W S34 BT.  
20" Fir N.21°W., 15.5 ft. scribed T24S R2W S33 BT.  
Note - Hand held  
Lat: 43°26.208 Long: 122°55.936  
Compass decl. 15½°E.