

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2911)

-----

Set a basalt stone 16x12x10" 11" in the ground for ¼ sec. cor. marked ¼ on W face, from which

- A fir, 12" dia., bears S.35°E., 25 lks., mkd: ¼ S BT.
- A fir, 15" dia., bears N.75°W., 11 lks., mkd: ¼ S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13295-6)

-----

The ¼ sec. cor. of secs. 33 & 34, monumented with a basalt stone 13x13x9" firmly set marked ¼ on W face, from which the orig. BTs:

- A fir, 18: dia., bears N.70°W., 11 lks., blazed healed. (Rec. bearing N.75°W.)
- A fir snag, 12" dia., bears S.36°E., 22 lks., blaze partially healed, wit scribe marks ¼ S visible. (Rec. bears S.35°E., 25 lks)

At the corner point

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd:

¼  
S 33|S 34  
1951

from which

- A fir, 28" dia., bears S.89°E., 55 lks., mkd: ¼ S34 BT.

Bury the orig. corner stone alongside the iron post.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 5/27/2008 - C.S. File 67/25-52

-----

Found - 2½" dia. brass cap marked as per record. BC/IP leans approx. S.13°W., 1.4 ft. from plumb position. Basalt stone not apparent.

- 28" now 28" dia., x 2 ft tall D.Fir stump, indeterminate scribe marks visible on partially healed blaze bears S.89°E., 36.3 ft. (agrees w/rec) 1951 BT.
- Orig. 15" dia., now 30" dia., D.Fir, tagged, no blaze visible bears N.70°W., 7.3 ft. (agrees w/rec) OBT

No trace of orig. SE BT.

Set - Returned BC/IP to plumb position without completely removing from ground.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

8" dia., chinquapin double blazed & scribed "¼ S34 CS BT" bears N.72°E., 27.0 ft.  
6" dia., D.Fir double blazed & scribed "¼ S34 CS BT" bears S.75¼°E., 20.0 ft.  
19" dia., D.Fir double blazed & scribed "¼ S33 CS BT" bears S.48¼°W., 18.4 ft.  
Note - Corner lies on moderate south facing slope. Mature timber to west.  
Compass decl. 16¼°E.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 5/2015 - C.S. File 65/89-3  
-----  
Found - GLO brass cap (properly mkd)  
9" Chincapin N.72°E., 27.0 ft. vis. scribe.  
7" D.Fir S.75°E., 20.0 ft. vis. scribe.  
19" D.Fir S.48°W., 18.4 ft. vis. scribe.  
31" D.Fir N.70°W., 7.3 ft. healed face.  
28"x2' tall D.Fir stump S.89°E., 36.3 ft. mostly rotten.  
Note - Corner is on moderate West slope approx. 200' west of road.  
Compass decl. 15½°E.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 12/2/2025 - C.S. File 67/61-44  
-----  
Found - 2½" BLM Brass cap proj 6".  
Burned, dead, 9" chinquapin N.72°E. 27.0 ft. blaze burned out.  
Burned, rotted 8½" x 1½ ft. D. fir stump S.75°E. 20.0 ft. Scribe 3 and notch visible.  
Burned, dead 20" D. Fir S.48°W. 18.4 ft. fully healed double blaze. Add 3½" mag nail left side center.  
Burned, dead 33" D. Fir N.70°W. 7.3 ft. healed face.  
26"x1 ft. D.fir stump S.89°E. 36.3 ft. mostly gone.  
Add 3½" mag nail right side center to chinquapin and N.W. fir BT.  
New - Burned, dead 40" D. Fir N.30°W. 15.0 ft. 3½" mag nail right side center.  
Notes - Area badly burnt 9/2020.  
Compass decl. 14¼°E.  
TRIMBLE GEO XT POSITION  
43.44235353 N.  
122.93154568 W.