

PRIMARY CORNER DESCRIPTION W.C. Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2911-2)

Set a basalt stone 15x12x10", 10" in the ground for the cor. to secs. 27, 28, 33, & 34, marked with 1 notch on the S & 3 notches on E edges, from which

- A Chinquapin, 10" dia., bears N.31°E., 20 lks., mkd: T24S R2W S27 BT.
- A Hemlock, 6" dia., bears S.28°E., 14 lks., mkd: T24S R2W S34 BT.
- A Hemlock, 8" dia., bears S.15°W., 17 lks., mkd: T24S R2W S33 BT.
- A Hemlock, 8" dia., bears N.60°W., 14 lks., mkd: T24S R2W S28 BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13296-7)

The cor. of secs. 27, 28, 33, & 34, monumented with a basalt stone, 16x14x10" firmly set, marked with 1 notch on S & 3 notches on E edges, from which the orig. BTs:

- A Chinquapin, 10" dia., bears N.31°E., 18 lks., partial scribe marks visible in rotted blaze. (Rec. dist. 20 lks.)
- A Hemlock, 12" dia., bears S.25¼°W., 14 lks. blaze healed. (Rec. bearing S.28°E.)
- A Hemlock, 12" dia., bears S.15½°W., 17 lks., scribe marks T24S R2W S33 visible. (Rec. bearing S.15°W.)
- A Hemlock, 12" dia., bears N.64½°W., 14 lks., blaze healed. (Rec. bearing N.60°W.)

At the corner point
 Set an iron post, 36" long, 2" dia., 24" in the ground, to solid rock & in a mound of stone, 4 ft. base to top, with brass cap mkd:

T24S	R2W
<u>S 28</u>	<u>S 27</u>
S 33	S 34
1951	

from which

- A Hemlock, 22" dia., bears N.9¼°E., 84 lks., mkd: T24S R2W S27 BT.
- A Hemlock, 20" dia., bears S.33¼°W., 43 lks., mkd: T24S R2W S33 BT.

Bury the orig. corner stone alongside the iron post.

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Weyerhaeuser, Glen McChesney - Oct. 1957 - C.S. File 53/110-9

Found - GLO Brass cap
10" Chinquapin, face rotten leans to SW, N.33°E.,
12.0 ft.
12" Hemlock, S.27°E., 8.7 ft.
14" Hemlock, S.15°W., 10.5 ft.
14" Hemlock, N.61°W., 8.7 ft.
18" Hemlock, S.38°W., 28.0 ft., 1951.
22" Hemlock, N.12°E., 54.8 ft., 1951.
New - 56" Fir stump, N.47°E., 18.5 ft., "W" nail & plate.
28" Sugar pine, S.43°E., 33.0 ft., "W" nail & plate.
Added "W" nail & plate to 1951 new BTs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - June
1967 - C.S. File 52/42-52

Post card sent to office -
Corner has slid out but BTs still present:
22" Hem. N.16°E., 52.7 ft. good scribe, resurvey BT,
tree dying.
20" Hem. S.33¼°W., 28.4 ft. good scribe, resurvey BT,
tree alive.

Note - N.37°E., on "W" tag. No orig. BTs fd. due to slide.

Tracy's comments on card -
Brass cap not found.
This area subject to earth slides - BTs don't agree
bearing & dist.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy -
Pete L. Earle - 10/14/1974 - C.S. File 57/8-12

Found - One BT intact, a 22" now 24" Hemlock snag mkd. by
BLM crews in 1951 during a resurvey. This area
has experienced landslide activity & as a result,
there is no other evidence of the orig. or
subsequent surveys.

We therefore set a witness corner 85 ft. South of the true
corner point as determined from the only remaining BT A 24"
Hemlock snag bearing N.9¼°E., 55.4 ft. with scribing "T24S
R2W S27 BT plainly visible on an unhealed blaze.

Set - At the witness corner we set a 1"x30" iron pipe, 28" in
the ground with a brass cap attached mkd:

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION W.C. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

COUNTY SURVEYORS OFFICE
T24S R2W
S 28 | S 27
S 33 | S 34
WITNESS COR.
85 FT NORTH
TO TRUE COR
1974
New BTs- A 12" R.Cedar bears N.35°E., 30.3 ft., scribed "WC
T24S R2W S33 CS BT"
An 18" D.Fir bears S.54°W., 23.9 ft., scribed "WC
T24S R2W S33 CS BT"
A 26" Hemlock bears N.64°W., 42.5 ft., scribed "WC
T24S R2W S33 CS BT"

FD BC & 3 BTs, D. Edwards 5/2008 - M156-7
Fd ok by R. Quimby 5/2015 - C.S. File 65/89-1