

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400220

PRIMARY CORNER DESCRIPTION S 1/16 S28|S27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V.W. Hosford - For: Evans Products Company - 11-12/1953 - CS 40/110-002  
-----  
Set - 4" cedar post for corner, from which  
A cedar, 18" dia., bears N.16°E. 30.8 ft. mkd 1/16  
S27 -PS253 -BT  
A cedar, 24" dia., bears N.50°W. 41.6 ft. mkd 1/16  
S28, -PS 253 -BT

Glen McChesney - For: Weyerhaeuser Timber Company - 10/24/1957 - CS 53/110-7  
-----  
Found - 24" Cedar, N.49°W. 40.9 ft. (Rec. N.50°W. 41.6 ft)  
Scribe visible, good condition. Added "W" nail and plate  
18" Cedar, N.17°E. 30.3 ft. (Rec. N.16°E. 30.8 ft)  
Scribe visible, good condition. Added "W" nail and plate  
Note - Pipe (Hosford's) 20° magnetic declination.  
At East edge of cat fire trail.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and  
Jeff Lorsung - 12/11/2025 - C.S. File 67/61-53  
-----  
Found - 1¼" I.D. iron pipe, proj. 13".  
Burned - broken 24" cedar stump N.49°W. 40.9 ft. to W nail.  
Dead 32" cedar N.17°E. 32.6 ft. (Rec 30.3 ft.) Add  
3½" mag nail, right side center.  
New - 18" sawn fir stump S.30°W. 17.3 ft. Add 3½" mag  
nail, top center.  
Notes - Area burnt 9/2020  
Corner is approx. 400 ft. East of logging landing in  
flat clearcut.  
Compass decl. 14¼°E.  
TRIMBLE GEO XT POSITION  
43°.45272407 N.  
122°.93165540 W.