

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2919)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 9, 10, 15, & 16, marked T24S S10 on NE, R2W S15 on SE, S16 on SW, S9 on NW faces, with 4 notches on S & 3 notches on E edges; from which
A hemlock, 30" dia., bears N.35°E., 113 lks., mkd: T24S R2W S10 BT.
A vine maple, 6" dia., bears S.69°E., 52 lks., mkd: T24S R2W S15 BT.
A cedar, 24" dia., bears S.55°W., 52 lks., mkd: T24S R2W S16 BT.
A yew, 9" dia., bears N.10°W., 52 lks. mkd: T24S R2W S9 BT

Douglas Co. Surveyors Office - V. "Ray" Tracy - V. Perron - Glenn McChesney (WEYCO) - Oct. 1970 - C.S. File 54/27-240

Found - Orig. 30" now 34" Hemlock, N.35°E., 8.6 ft., (rec. 74.6) ring count difficult, very fine, about 60 to 80 years, open scribe visible.
Orig. 24" now 36" Cedar, down, S.55°W., 34.3 ft., open & find scribe.
No trace of Yew wood BT to NW
Decayed stub at locus of SE Vine Maple BT.
Old blazed lines N-S-E & W would also bear out this location.
Set - Brass cap at cor. mkd: County Surveyors Office 1970 T24S R2W S 9 | S 10 S 16 | S 15
New BTs- 61" D.Fir N.41°W., 23.6 ft., mkd: "T24S R2W S9 CS BT" (21.2 ft. to "W" nail)
8" Hemlock S.6°E., 33.8 ft., "T24S R2W S16 CS BT"
Add "W" to orig. BT to NE.
This area to be clear cut in future.