

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO recs Vol. 7 Pg 2912)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S on N face, from which:

A cedar, 10" dia., bears N.44°E., 27 lks., mkd: 1/4 S BT.

A cedar, 10" dia., bears S.68°E., 26 lks., mkd: 1/4 S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13297)

The 1/4 sec. cor. of secs. 27 & 34 determined at the record distance from the orig. BTs:

A cedar, 12" dia., bears N.45 1/4°E., 27 lks., blaze healed. (Rec. bearing N.44°E.)

A cedar, 8" dia., bears S.67°E., 6 lks., scribe mark 1/4 S BT visible. (Rec. bearing S.68°E.)

At the corner point

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap marked:

1/4 $\frac{S\ 27}{S\ 34}$
1951

from which

A fir, 14" dia., bears N.54 1/2°E., 64 lks., mkd: 1/4 S27 BT.

A hemlock, 12" dia., bears S.55 1/2°E., 50 lks. mkd: 1/4 S34 BT

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 5/27/2008 - C.S. File 67/25-53

Found - 2 1/2" dia., brass cap mkd. as per record, leaned over approx. S.60°W., 1.7 ft.

12" Hemlock, now 1 ft. tall from center of tree, bears S.55 1/2°E., 33.0 ft. (agrees w/rec) 1951 BT.

No trace found of 1951 NE BT.

New - Returned BC/IP to plumb position without completely removing.

Double trunk D.Fir, southerly trunk is 14" dia., & is double blazed & scribed "1/4 S27 CS BT" center of root crown bears N.50 1/4°E., 29.6 ft.

9" dia., Hemlock double blazed & scribed "1/4 S34 CS BT" bears S.65 1/2°E., 1.7 ft.

10" dia., D.Fir double blazed & scribed "1/4 S34 CS BT" bears S.86 1/4°W., 11.8 ft.

20" dia., D.Fir double blazed & scribed "1/4 S27 CS BT" bears N.12°W., 5.8 ft.

Note - Compass decl. 16 1/4°E.