

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2919-20)</p> <p>-----</p> <p>Set a basalt stone 12x10x6" 8" in the ground for ¼ sec. cor. marked ¼ on N face, from which</p> <p> A hemlock, 20" dia., bears S.7°W., 33 lks., mkd: ¼ S BT.</p> <p> A hemlock, 14" dia., bears N.12°W., 35 lks., mkd: ¼ S BT.</p>
<p>Weyerhaeuser Co. - Oct. 1964 - C.S. File 53/110-</p> <p>-----</p> <p>Found - 6"x10"x12" basalt stone, lying on top of ground, chisel marks "¼".</p> <p> 20" Hemlock, now 18" S.7°W., 21.8 ft. scribing visible (Orig. BT)</p> <p> 14" Hemlock, now 20" N.12°W., 23.1 ft., scribing visible.</p> <p>Reset - Stone in the ground, 3"x3"x4' hemlock post.</p> <p> 18" Hemlock S.6°W., 21.3 ft., orig. BT added "W" nail & plate.</p> <p> 68" Fir, N.80°E., 43.0 ft., added "W" nail & plate.</p>
<p>Douglas Co. Surveyors Office - John Powell - 8/28/1970 - C.S. File 54/27-215</p> <p>-----</p> <p>Found - 1" iron pipe, no record.</p> <p>Note - A man from Weyerhaeuser has been in area for a couple of weeks doing some work possibly he put it there.</p>
<p>Fd. Ok by Nick Juliano, 11/1978 - C.S. File 58/184-2</p> <p>-----</p> <p>Found - Stone mkd "¼"</p> <p> 28" hemlock, S.6°W., 21.8' scribe vis., W.CO. tag.</p> <p> 20" hemlock, N.9°W., 23.1', scribe vis.</p> <p> 68" fir, N.80°E., 43.0', W.CO. nail & tag.</p>
<p>Daniel Baker - For: Weyerhaeuser Co. - 10/2016 - M172-71</p> <p>-----</p> <p>Found - 12"x6"x10" Basalt stone mkd "¼" on top.</p> <p> 68" Fir stump, N.80°E., 43.0' to "W" nail in face, 1964 Weyerhaeuser BT</p> <p> Rotten hemlock stump, S.6°W., 21.8' to center, OBT</p> <p> Rotten hemlock stump, N.9°W., 23.1' to center, OBT (Stone placed alongside new corner monument.)</p> <p>Set - 5/8"x36" rebar with 2½" alum. cap in place of stone.</p> <p> 11" Fir, N.35°E., 6.1' to spike side/center-scribed "¼S10BT"</p> <p>continued next page</p>

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

16" Fir, S.24°E., 13.5' to spike side/center-scribed
"¼S15BT"
14" Fir, S.36°W., 3.4' to spike side/center-scribed
"¼S15BT"
13" Fir, N.27°W., 10.6' to spike side/center-scribed
"¼S10BT"