

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2904)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 22, 23, 36, & 27, marked T24S S23 on NE, R2W S26 on SE, S27 on SW, S22 on NW faces, with 2 notches on the S & E edges; from which

- A fir, 6" dia., bears N.42°30'E., 11 lks., mkd: T24S R2W S23 BT.
- A maple, 6" dia., bears S.51°E., 21 lks., mkd: T24S R2W S26 BT.
- A hemlock, 6" dia., bears S.34°30'W., 14 lks., mkd: T24S R2W S27 BT.
- A cedar, 6" dia. bears N.57°W. 12 lks. mkd: T24S R2W S22BT

V.W. Hosford - April 1952 - M 12-55

-----

Found - 4 orig. BTs  
BTs for secs. 22 & 23 dead & down.  
BT for sec. 26 dead but standing.  
BT for sec. 27 alive & standing.

Re-established Corner as shown -

- 1½" iron pipe.
- 12" Fir, mkd: T24S-S23 PS253 BT, N.52½°E., 30.8 ft.
- 12" Hemlock mkd: R2W-S26 PS253 BT, S.17°E., 12.0 ft.
- 12" Hemlock mkd: T24S-S27 PS253 BT, S.42°W., 9.0 ft.
- 14" Cedar mkd: R2W-S22 PS253 BT, N.21°W., 16.3 ft.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1624, surveyed Aug./Oct. 1991 - (DCSO records Vol. 51 Page(s) 19240-1)

-----

The cor. of secs. 22, 23, 26 & 27, perpetuated & recorded by Hosford, in 1952, from original evidence no longer in existence, monumented with an iron pipe, 1½" diam., firmly set, projecting 8" above ground, from which the remains of the bearing trees mkd. by Hosford:

- A fir, 20" dia. bears N.53½°E., 47 lks., with healed blaze
- A hemlock snag, 12" dia., bears S.16¾° E., 18 lks., with scribe marks R2W S26 PS253 BT visible on open blaze.
- A cedar, 24" dia., bears N.21½°W., 24½ lks., with fragmentary scribe marks visible on partially healed blaze.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, directly over the 1½" dia. iron pipe, with brass cap mkd.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T24S R2W  
S 22 \* S 23  
S 27 \* S 26  
1991

from which new bearing trees  
A hemlock, 15" dia., bears S.59½°E., 25 lks., mkd. T24S  
R2W S26 BT.  
A hemlock, 17" dia., bears S.43¼°W., 40 lks., mkd. T24S  
R2W S27 BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless  
steel post.

Fd. Ok by R.Quimby, 3/2013, Note on the bottom of CS 65/78-23