

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2905)

Set a basalt stone 12x10x8", 8" in the ground for cor. to secs. 14, 15, 22, & 23, marked with 3 notches on S & 2 notches on E edges, from which
A yew, 12" dia. bears N.32°E. 27 lks. mkd: T24S R2W S14 BT
A fir, 40" dia. bears S.52°E., 7 lks. mkd: T24S R2W S23 BT
A cedar, 24" dia., bears S.15°W., 24 lks., mkd: T24S R2W S22 BT
A yew, 10" dia. bears N.73°W. 14 lks. mkd: T24S R2W S15 BT

V.W. Hosford - Sept. 1957 - C.S. File 42/306-6

Before logging in this area I fd. the two yew & the one cedar BTs, described in the orig. notes, in good condition. The orig. marked stone corner was gone, & the 40" Fir BT was a windfall. After logging, only the orig. Cedar BT remained. From this tree I determined the position of the corner & drove a 2" iron pipe 30" long, 18" in ground, from which:
A hemlock 28" dia., bears S.56½°E., 77.9 ft., mkd: T24S R2W S23 PS 253 BT.
A cedar 30" dia., bears S.15°W., 15.8 ft., (orig. BT) mkd: T24S R2W S22 PS 253 BT.
A yew 12" dia., bears N.70°W., 75.4 ft., mkd: T24S R2W S15 253 BT.
No suitable tree remained standing in NE quadrant.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - July 1968 - C.S. File 54/27-221

Found - 2" iron pipe & BTs as recorded in 1957.
28" now 29" Hemlock, alive, S.56½°E., 77.9 ft., scribe visible on unhealed blaze.
30" now 31" Cedar, alive S.15°W., 15.8 ft., scribe in poor condition. Rescribe "T24S R2W S22 CS BT"
12" Yew, alive, N.70°W., 75.4 ft., scribe visible on unhealed blaze.
No trees available to NE
Set - Brass cap at cor. mkd: County Surveyors T24S R2W
Office S 15 | S 14
1968 S 22 | S 23
Note - This corner lies 50 ft. N. of small creek 3 ft. wide, course S.60°W.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1624, surveyed Aug./Oct. 1991 - (DCSO records Vol. 51 Page(s) 19242)

The cor. of secs. 14, 15, 22 & 23, perpetuated & recorded by Hosford, in 1957, further perpetuated and recorded by Tracy, in 1968, monumented with an iron post, 1½" diam., firmly set, projecting 9" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T24S
S 15 | S 14
S 22 | S 23

R2W
1968

from which an original bearing tree

A cedar, 41" dia. bears S.15°W., 24 lks., with fragmentary scribe marks visible on partially healed blaze. and bearing trees mkd. by Hosford

A hemlock, 34" dia., bears S.57¾°E., 117 lks., with scribe marks T24S R2W S23 PS253 BT visible on open blaze.

A yew, 18" dia. bears N.71¼°W., 115 lks., with fragmentary scribe marks visible on partially healed blaze. and a new bearing tree

A cedar, 7" dia., bears N.65°E., 27 lks., mkd. T24S R2W S14 BT.