TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5 1893 - (DCSO rec Vol 7 Pgs 2908-9)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:
A yew, 6" dia., bears S.85°E., 33 lks., mkd: ¼ S BT.
A yew, 7" dia., bears N.20°W., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - W. Penley & J. Heritage - Sept. 1970 - C.S. File 54/27-231

Found - 6" now 9" Yew, S.70°E., (rec. S.85°E.) 21.8 ft., shows old axe work, rotten face.
7" now 12" Yew, N.20°W., 13.9 ft., scribing fd. "T" & other marks, rotten face.
Set - Brass cap at cor. mkd: County Surveyors Office 1970 T24S R2W ¼ S 10 | S 11
Reblazed & rescribed:
9" Yew S.70°E., 21.8 ft. mkd: "¼ S11 CS BT"
12" Yew N.20°W., 13.9 ft., mkd: "¼ S10 CS BT"
Topography sheet for this corner is way off. Calls on creek & top of ridge OK

Glenn McChesney, Weyerhaeuser Co. - 1976 - C.S. File 59/11-2

Found - DCSO brass cap.
Orig. BTs as recorded by DCSO
New - 36" Fir stump N.6°E., 26.0 ft., "W" nail & plate.
52" Fir S.68°W., 7.6 ft., "W" nail & plate.

FD. OK (2 Yew OBTS) BLM 3/17/1992 - C.S. File 63/140-1

Russell Badgley - For: Weyerhaeuser Co. - 11/2020 - M178-14

Found - A 1½" IP by DCSO in 1970 per CS file 54/27-231, firmly set and projecting 4" above the ground, with a 2½" brass cap (properly) mkd
From which the original BTs -
A 13" Yew bears S.70°E., 21.8 ft (S.70°E., 21 8')
A 16" Yew bears N.23°30'W., 13.3 ft (N.20°W., 13.9')
BTs by McChesney in 1976 -
A 40" D.Fir stump bears N.7°E., 27 1 ft and the "W" nail bears N.4°15'E., 26.1 ft (N.6°E., 26.01')
New BTs- A 10" D.Fir bears N.84°30'E., 21 8 ft mkd "¼ S11 BT" on double blaze
A 12" D.Fir bears S.27°00'W., 7.9 ft mkd "¼ S10 BT" on double blaze
NAD83(2011) LAT:43°30'04.15377"N LONG: 122°54'43 21313"W