

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2910)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:

- A fir, 30" dia., bears N.29°W., 40 lks., mkd: ¼ S BT.
- A fir, 40" dia., bears N.78°30'E., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - W. Penley & J. Heritage - Aug. 1970 - C.S. File 54/27-229

Found - 30" now 42" fir, N.29°W., 26.4 ft., shows good scar.
40" now 58" fir, N.78½°E., 6.6 ft., shows good scar.

Set - Brass cap at cor. mkd: County Surveyors T24S R2W
Office 1970 ¼ S 3|S 2

Bearing trees OK & tagged.

Russell Badgley - For: Weyerhaeuser Co. - 11/2020 - M178-14

Found - A 1½" IP by DCSO in 1969 per CS file 54/27, firmly set with a 12" high collar of stone & projecting 4" above the collar, with a 2½" brass cap mkd

From which the original BTs

- A 42" D.Fir stump capped with tin bears N.28°30'W., 26.7 ft w/healed blaze (N.29°W., 26.4')
- A 58" rotting D.Fir stump bears N.74°15'E., 6.7 ft w/healed blaze (N.78½°E., 6.6')

New BTs-

- A 10" D.Fir S.62°45'E., marked "¼ S2 BT on double blaze.
- A 11" D.Fir bears S.36°W., 5.0 ft. marked "¼ S3 BT" on double blaze.
- A 11" D.Fir bears N.46°W., 8.0 ft. marked "¼ S3 BT" on double blaze.
- A 13" D.Fir bears N.10°30'E., 27.8 ft. marked "¼ S2 BT" on double blaze.

NAD83 (2011)
Latitude: 43°30'55.67751"N Longitude: 122°54'45.72417"W