

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2173)

-----  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 34 and 35, mkd. T23S S35 on NE.; R2W S2 on SE.; T24S S3 on SW.; S34 on NW. faces, with 2 notches on E. and 4 notches on W. edges, from which  
A Fir 36" dia., bears N.55°E., 14 lks. dist. mkd. T23S R2W S35 BT.  
A Fir 36" dia., bears S.50°E., 24 lks. dist. mkd. T24S R2W S2 BT.  
A Chinquapin 16" dia., bears S.22°W., 16 lks. dist. mkd. T24S R2W S3 BT.  
A Yew 15" dia., bears N.53°W., 38 lks. dist. mkd. T23S R2W S34 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2180)

-----  
(78.50 chs.)  
The old sec. cor., a post bears South, 3.90 chs., I destroyed this post, also the marks on old bearing trees.  
(80.00 chs. West)  
Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 34 and 35, mkd. T23S S35 on NE.; R2W S2 on SE.; T24S S3 on SW.; and S34 on NW. faces, with 2 notches on E. and 4 notches on W. faces, from which  
A Chinquapin 8" dia., bears N.85°E., 20 lks. dist. mkd. T23S R2W S35 BT.  
A Fir 24" dia., bears S.68°E., 32 lks. dist. mkd. T24S R2W S2 BT.  
A (?) 30" dia., bears S.38°W., 18 lks. dist. mkd. T24S R2W S3 BT.  
A Fir 24" dia., bears N.46°30'W., 38 lks. dist. mkd. T23S R2W S34 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 29, 1969 - C.S. File 54/27-163

-----  
Found - Orig. 8" now 12" Chinquapin, alive, N.85°E., 13.2 ft., scribe visible.  
Orig. 24" now 30" Fir, alive, S.48°E., 21.1 ft. (Rec. S.68°E.), shows good scar.  
Orig. 24" now 28" Fir, alive, S.38°W., 11.9 ft., shows good scar. We rescribed "T24S R2W S3 CS BT".  
(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T23-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. 24" now 28" Fir, alive, N.46½°W., 25.1 ft., shows good scar.  
Set Brass cap at cor. mkd: County Surveyors Office  
T23S R2W S 34 | S 35  
T24S S 3 | S 2  
1969  
New BT - 34" D.Fir N.66°E., 28.0 ft. mkd. T23S R2W S35 CSBT.  
Corner lies on very steep, southerly slope in dense rhododendron, vinemaple and old growth fir.

Russell Badgley - For: Weyerhaeuser Co. - 11/2020 - M178-14  
-----  
Found - A 1½" IP by DCSO in 1969 per CS 54/27-163, firmly set and projecting 10" above the ground, with a 2½" brass cap mkd  
From which the original BTs  
A 35" D.Fir bears S.48°45'E., 21.2 ft w/healed blaze (S.48°E., 21.1')  
A 40" D.Fir bears S.28°45'W., 10.9 ft w/healed blaze (S.38°W., 11.9')  
New BT - A 5" Chinquapin bears N.12°15'W., 7.6 ft bark scribed "X BT"  
New reference monument -  
A ⅝"X30" IR with 2' aluminum cap mkd "RM1 LS70716" bears N.63°13'25"E., 12.70 ft  
NAD83 (2011)  
Latitude: 43°31'18.33459"N Longitude: 122°54'46.00304"W