

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 26

Alias	Description

<p>V.W. Hosford - April 1952 - M 12-55</p> <p>-----</p> <p>Set - 1½" I.P. 12" Cedar, mkd: ¼ S26 PS253 BT, bears S.65½°W. 30.2 ft. 14" Hemlock, mkd: ¼ S26 PS253 BT, bears N.82½°E., 37.1 ft.</p>
<p>Ron Quimby - Crew: Jeremy Leonard, Derek Feigel & Nolan Fromdahl - 4/1/2013 - C.S. File 65/78-23</p> <p>-----</p> <p>Found - Hemlock snag scribed "¼ S 26 PS (unreadable) BT" - tree was blazed & scribed "¼ S26 PS253 BT" per M12-55 5/8"x30" iron rod with alum. cap stamped "ROSEBURG RESOURCES COMPANY"</p> <p>New - 13" Fir blazed & scribed "C¼ S26 BT" bears N.60°13'W., 23.2 ft. 14" Fir blazed & scribed "C¼ S26 BT" bears N.43°19'E., 22.1 ft 10" Fir blazed & scribed "C¼ S26 BT" bears S.32°42'E., 16.8 ft. 19" Fir blazed & scribed "C¼ S26 BT" bears S.37°06'W., 15.7 ft.</p> <p>Note - Corner is located on the easterly side of a very steep draw with windfall trees surrounding it. Ground is somewhat rocky & has been logged in the past. Compass decl. 15½°E.</p>
<p>Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 5/2018 - C.S. File 65/101-35</p> <p>-----</p> <p>Found - 5/8" I. Rod with alum cap mkd: ROSEBURG RESOURCES COMPANY 15" D.Fir N.43°E., 22.1 ft. vis. scribes. 12" D.Fir S.33°E., 16.8 ft. vis. scribes. 13" D.Fir N.60°W., 23.2 ft. vis. scribes, now 6' tall stump. 19" D.Fir S.37°W., 15.7 ft. vis. scribes, now 6' tall stump.</p> <p>New BTS- 12" Hemlock S.88°E., 28.1 ft scribed C¼ S26 BT 18" Fir N.64°E., 33.2 ft. scribed C¼ S26 BT</p> <p>Note - Corner is on East edge of clearcut unit approx. 700 ft. East of switch back in gravel road. Compass decl. 15½°E.</p>
<p>Fd Ok by R Quimby 10/2020 - C.S. File 65/106-51</p>