

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2904-5)

Set a basalt stone 12x8x8" 8" in the ground for ¼ sec. cor. marked ¼ on N face, from which

A hemlock, 6" dia., bears N.7°30'E., 16 lks., mkd: ¼ S BT.

A hemlock, 18" dia., bears S.40°W., 22 lks., mkd: ¼ S BT.

V.W. Hosford - April 1952 - M 12-55

Found - Orig. marked stone monument & both bearing trees alive & standing.

Douglas Co. Surveyors Office - John Powell - Willie Penley - Aug. 1970 - C.S. File 54/27-228

Found - 18" now 24" hemlock, S.40°W., 14.5 ft., shows good scar.

6" now 12" hemlock, N.7½°E., 10.6 ft., opened for scribe "S4"

12x8x8 stone at cor. mkd: County Surveyors T24S R2W

Office	¼	<u>S 23</u>
1970		S 26

New BT - 12" hemlock N.32°W., 24.3 ft., mkd: "¼ S23 CS BT"

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1624, surveyed Aug./Oct. 1991 - (DCSO records Vol. 51 Page(s) 19239-40)

Beginning at the ¼ sec. cor. of secs. 23 & 26, perpetuated & recorded by Hosford, in 1952, further perpetuated & recorded by Powell, in 1970, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T24S	R2W
	¼
	<u>S 23</u>
	S 26
	1970

from which the remains of the original bearing trees

A hemlock, 17" dia., bears N.4¾°E., 16 lks., with scribe mark S visible on opened blaze. (Rec. N.7½°E.)

A root hole, bears S.26°W., 22 lks., with uprooted 26 in. dia. hemlock alongside, with healed blaze. (Rec. S.40°W.)

and the remains of a bearing tree mkd. by Powell

A hemlock snag, 14" dia., bears N.31°W., 37 lks., with healed single blaze. continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree

A hemlock, 16" dia., bears S.43³/₄°E., 64 lks. mkd. ¹/₄ S26 BT

From this point, the BLM, Geodetic Control Station No. EC41118, at Lat. 43°27'52.348"N., Long. 122°54'02.546"W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N.49°46'10"E., 3.916 chs. (mean bearing & sea level distance), monumented with an aluminum cap, 2¹/₂" dia., firmly set in concrete flush with the ground, with top mkd. EC41118 GPS 1991.

Fd. Ok by R.Quimby, 3/2013, Note on the bottom of CS 65/78-23