

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2906)

-----

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:

- A hemlock, 5" dia., bears N.35°E., 32 lks., mkd: ¼ S BT.
- A hemlock, 24" dia., bears S.17°W., 40 lks., mkd: ¼ S BT.

V.W. Hosford - Sept. 1957 - C.S. File 42/306-3

-----

After logging in Sec. 14, both orig. BTs were in good condition.

At the true point of the corner, I drove a 1½" iron pipe 24" long, 16" in the ground.

Ron Quimby - Crew: N. Fromdahl & J Ogden - 5/2019 - C.S. File 65/102-48

-----

Found - 1½" I.Pipe  
28" hemlock N.35°E., 21.1 good scar.

New - 7" W.Fir S.82°E., 18.5 scribed ¼ S23 BT.  
8" Hemlock S.31°E., 11.5 ft. scribed ¼ S23 BT.  
6" alder, West 7.0 ft. scribed ¼ S14 BT.  
6' alum post 2.0 ft. East.

Note - Compass decl. 15½°E.