

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2908)

-----  
Set a basalt stone 12x9x9" 8" in the ground for ¼ sec. cor. marked ¼ on N face, from which  
A fir, 30" dia., bears S.52°E., 45 lks., mkd: ¼ S BT.  
A chinquapin, 6" dia., bears N.28°E., 28 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1969 - C.S. File 54/27-249

-----  
Found - No trace of corner stone.  
Orig. 30" now 35" fir, alive, S.52°E., 29.7 ft., shows good scars. We rescribe "¼ S14 CS BT"  
Orig. 6" now 6" chinquapin snag, N.28°E., 18.5 ft., fragmentary scribe visible on decayed axe blaze.  
Set - Brass cap at cor. mkd: County Surveyors T24S R2W  
Office ¼ S 11  
1969 S 14  
New BT - 8" Cedar N.86°W., 33.9 ft., mkd: "¼ S11 CS BT"  
This corner lies on bench, gently sloping SW.

Ron Quimby - Crew: Fromdahl & Olsen - 6/2014 - C.S. File 65/82-42

-----  
Found - DCSO Brass cap (properly mkd)  
43" Fir S.52°E., 29.7 ft good scar.  
New - 9" Fir N.68°E., 21.6 ft. scribed ¼ S11 BT.  
13" Fir S.12°W., 18.4 ft. scribed ¼ S14 BT.  
18" Fir N.35°W., 15.1 ft. scribed ¼ S11 BT.  
Compass decl. 15½°E.