

PRIMARY CORNER DESCRIPTION NE Cor. Tract 39 (Sec. 35)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13289)

Point for the NE cor. of Tract No. 39, sec. 35
Set an iron post, 28" long, 2½" dia., 32" in the ground, and in a small mound of stone, with brass cap mkd.

T 24 S R 2 W
S 35 | S 36
TR 39 |
1963

from which

- A sugar pine, 13" dia., bears S.80¼°W., 90 lks., mkd: TR39 S35 BT.
- A fir, 16" dia., bears N.31½°W., 37 lks., mkd: S35 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - Dec. 9, 1986 - C.S. File 62/38-2

Found - 1963 GLO 2½" dia., by 28" long IP with brass cap leaning 7" west of plumb position. Cap properly marked.

13" now 14" dia., down & out of ground sugar pine with scribing visible "TR 39 S35 BT" bears S.85°W., 63.6 ft. to center of road wad. Possible stump hole at rec. bearing & dist. (S.80¼°W., 59.4 ft.)

NW BT gone. Stump hole at rec. bearing & dist. (N.31½°W., 24.4 ft.)

Set - Position of BC/IP straightened to plumb. A 2 ft. mound of stone placed along west edge of IP. (Sketch in file)

The NW cor. TR 40, an iron pipe & brass cap bears S.21½°W., 64.7 ft.

New BTs- 9" dia., cedar double blazed & scribed "S35 CS BT" bears S.38½°E., 35.5 ft.

10" dia., D.Fir double blazed & scribed "S35 CS BT" bears N.73°W., 56.9 ft.

36" dia., 5½ ft. high D.Fir stump with a boat spike stamped "CS BO 1 1986" driven through BT tag in top of stump. Spike bears N.28°E., 34.6 ft.

18" dia., 3 ft. high D.Fir stump with a boat spike stamped "CS BO 2 1986" driven through BT tag in top of stump. Spike bears S.23°W., 8.3 ft.

Corner lies at SW corner of new clear cut on steep NW slope.