TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2891)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:
A fir, 6" dia., bears N.41°E., 9 lks., mkd: ¼ S BT.
A fir, 7" dia., bears S.32°W., 16 lks., mkd: ¼ S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13289)

The ¼ sec. cor. of secs. 35 & 36, determined at rec. bearing & dist. from the orig. SW BT:
A fir, 20" dia., bears S.32°W., 16 lks., partial scribe marks visible.
At the corner point
Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap marked: ¼
S 35|S 36
1951
from which
A fir, 14" dia., bears N.77½°E., 51 lks., mkd: ¼ S36 BT.
A fir, 14" dia., bears N.63°W., 56 lks., mkd: ¼ S35 BT.

Fd. Ok 2/1954, Ben Irving - C.S. File 45/257 - See file for add'l info.

Fd. 3 BTs & BC 3/1968 DCSO C.S. File 54/27-144