

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Corner Secs 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2891)

Set basalt stone 15x10x5", 10" in the ground for cor. to secs. 25, 26, 35, & 36 marked with 1 notch on S & 1 notch on E edges, from which
A fir, 24" dia. bears N.55°E. 35 lks. mkd: T24S R2W S25 BT
A hemlock, 12" dia., bears S.63°E., 53 lks., mkd: T24S R2W S36 BT.
A fir, 36" dia. bears S.81°W. 22 lks. mkd: T24S R2W S35 BT
A fir, 18" dia. bears N.75°W. 53 lks. mkd: T24S R2W S26 BT

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13290)

The cor. of secs. 25, 26, 35, & 36, determined at record dist. from the orig. BTs:
A fir, 28" dia., bears N.60°E., 35 lks., blaze healed, edge of face under 57 yrs. overgrowth. (Rec. bearing N.55°E.)
A hemlock, 20" dia., bears S.57°E., 53 lks., partial scribe marks visible. (Rec. bearing S.63°E.)
A down fir, 30" dia., bears S.66¼°W., 22 lks., blaze healed. (Rec. bearing S.81°W.)
A down fir, 20" dia. bears N.75°W., 53 lks., blaze healed.

At the corner point
Set an iron post, 36" long, 2" dia., 24" in the ground to solid rock & in a mound of stone, 4 ft. base to top with brass cap marked:

T 24 S R 2 W
S 26 | S 25
S 35 | S 36
1951

from which
A hemlock, 12" dia., bears N.30½°E., 38 lks., mkd: T24S R2W S25 BT.
A fir, 20" dia., bears S.79°E., 68 lks., mkd: T24S R2W S36 BT.
A hemlock, 14" dia., bears S.67½°W., 71 lks., mkd: T24S R2W S35 BT.
A hemlock, 14" dia., bears N.67°W., 97 lks., mkd: T24S R2W S26 BT.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Corner Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 - C.S. File 52/42-56

Found - 1951 cadastral brass cap, firmly set & properly mkd. Orig. 28" Fir, alive, N.60°E., 23.1 ft. shows scar. Orig. 20" Hemlock, alive, S.57°E., 35.0 ft., shows scar.
12" Hemlock, N.30½°E., 25.1 ft., alive, scribe visible on unhealed blaze.
20" Fir S.79°E., 44.9 ft., alive blaze pitched over.
New BTs- 7" Hemlock S.30°W., 45.2 ft. mkd: T24S R2W S35 CS BT
8" D.Fir N.60°W., 41.0 ft., mkd: T24S R2W S26 CS BT
Note - This corner lies on steep west slope 150 ft. East of Rock Creek access road.

Fd Ok by R Quimby 10/2020 - C.S. File 65/106-51

Douglas Co. Surveyor's Office - Crew: Stephen J. Flauser and Jeff Lorsung - 11/6/2025 - C.S. File 67/61-38

Found - 2½" BLM brass cap proj 14" in rough mound of stone. Singed 35" D. Fir N.60°E. 23.1 ft. Shows scar.
29" Hemlock N.30½°E. 25.1 ft.
Burned, rotted 14" x 4 ft. fir stub S.79°E. 44.9 ft. exposed scribe S36.
Singed 30" Hemlock S.30°W. 45.2 ft. fully healed single blaze.
Sawn 26" x 2 ft. D. Fir stump N.60°W. 41.0 ft. fully healed single blaze.
Fd on ground, steel post. Reset on East edge of brass cap.
Notes - Mon on steep West slope 180± East of Rock Creek Access Rd.
Area Burnt 9/2020
Compass decl. 14¼°E.
Trimble GEO XT Position
43°26'56.513" N 122°53'37.312" W