

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2893)

Set a basalt stone 20x12x12", 15" in the ground for cor. to secs. 23, 24, 25, & 26, marked with 2 notches on S & 1 notch on E edges, from which

- A chinquapin, 6" dia., bears N.21°E., 44 lks., mkd: T24S R2W S24 BT.
- A laurel, 6" dia., bears S.81°E., 16 lks., mkd: T24S R2W S25 BT.
- A laurel, 6" dia., bears S.54°W., 6 lks., mkd: T24S R2W S26 BT.
- A fir, 40" dia., bears N.29°W., 63 lks., mkd: T24S R2W S23 BT.

Bruce Shaner - For: Evans Products Co. - Nov. 1962 - C.S. File 51/245

Found - Orig. 48" D.Fir BT with scribes visible, from which BT on a bearing of S.29°E., 41.6 ft.

- Set - 1"x36" galv. iron pipe, from which:
 - 24" D.Fir bears S.58°E., 31.4 ft., scribed "S 25 BT"
 - 10" D.Fir bears N.47°E., 33.0 ft., scribed "S 24 BT"
 - 14" D.Fir bears S.5°W., 37.0 ft., scribed "S 26 BT"

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 - C.S. File 54/27-243

Found - Orig. 40" now 48" Fir, N.29°W., 41.6 ft., alive, scribe visible.

- No trace of 1" I. Pipe called for in 1962.
- 24" D.Fir S.58°E., 31.4 ft., alive, good condition.
- 10" D.Fir N.47°E., 33.0 ft., alive, good condition.
- 14" D.Fir S.5°W., 40.0 ft., alive, good condition, (rec. dist. 37')

Set - Brass cap at cor. mkd: County Surveyors Office
 (in mound of stone) 1969

T24S	R2W
<u>S 23</u>	<u>S 24</u>
S 26	S 25

This corner lies in cutting corner, clear cut in sec. 24 at present.