

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2896-7)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
A fir, 7" dia., bears S.49°E., 5 lks., mkd: ¼ S BT.
A fir, 6" dia., bears S.40°W., 3 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1969 - C.S. File 54/27-245

Found - Orig. 7" now 13" Fir, alive, S.49°E., 3.3 ft., open & find scribe & reverse under approx. 70 yrs overgrowth.

No trace other Orig. BT.
Set - Brass cap at cor. mkd; County Surveyors T24S R2W Office 1969 ¼ S 14|S 13

New BTs- 13" D.Fir N.75°E., 15.5 ft., mkd: "¼ S13 CS BT"
14" D.Fir S.12°W., 61.6 ft., mkd: "¼ S14 CS BT"

This corner lies on Westerly slope about 660 ft. South of ridge top.

Ron Quimby - Crew: Fromdahl & Olsen - 6/2014 - C.S. File 65/82-44

Found - DCSO Brass cap (properly mkd)
16" Fir N.75°E., 15.5 ft. good scar.
18" Fir S.49°E., 3.3 ft. good scar.
27" Fir S.12°W., 61.6 ft. good scar.
New BT - 10" Fir N.48°W., 24.6 ft. scribed ¼ S 14 BT.
Note - Corner is on westerly slope approx. 300' west of road.
Compass decl. 15½°E.