

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2897)

Set a basalt stone 24x6x6" 18" in the ground for the cor. to secs. 11, 12, 13, & 14, marked 4 notches on S & 1 notch on E edges, from which

- A fir, 36" dia. bears N.85°E. 34 lks. mkd: T24S R2W S12 BT
- A fir, *" dia. bears S.33°E., 52 lks. mkd: T24S R2W S13 BT
- A fir, 6" dia. bears S.38°W., 34 lks. mkd: T24S R2W S14 BT
- A maple, 8" dia., bears N.73°W., 28 lks., mkd: T24S R2W S11 BT.

* No dia. given in official rec. per research 3/24/2004, JC DCSO

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1969 - C.S. File 54/27-238

- Found - Orig. corner stone with 4 notches on South & 1 notch on East edges.
- Orig. 36" now 42" fir, alive N.85°E., 22.4 ft., bark scribed.
- Orig. ? now 32" fir, S.33°E., 34.3 ft., alive, shows good scar.
- Orig. 6" now 13" Maple, alive, S.38°W., 22.4 ft., shows good axe scar. We rescribe "T24S R2W S14 CS BT" (Rec. Fir)
- Orig. 8" now 15" Maple, N.73°W., 38.3 ft., (rec. 18.5 ft.) face down & under logs, shows scar & was tagged, apparent 30 lk. error.

Set - Brass cap at cor. mkd: County Surveyors T24S R2W
 (Reset Corner stone Office S 11 | S 12
 alongside) 1969 S 14 | S 13

- New BTs- 20" Hemlock N.27°W., 29.9 ft., mkd: "T24S R2W S11 CS BT"
- 8" Hemlock N.54°E., 28.8 ft., mkd: "T24S R2W S12 CS BT"

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1533, surveyed May. 1990 - (DCSO records Vol. 50 Page(s) 18998-9)

The cor. of secs. 11, 12, 13 & 14, perpetuated by Tracy, in 1969, monumented with an iron post, 1½" diam., firmly set, projecting 6" above ground, with brass cap mkd.

continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

COUNTY SURVEYORS OFFICE

T 24 S

S 11 | S 12

S 14 | S 13

R 2 W

1969

from which the remains of the original bearing trees
A fir, 40" diam., bears N.85°E., 33 lks., with bark scribing T2 S W S BT visible. (Record, 34 lks.)
A fir, 28" diam., bears S.33°E., 46 lks., with healed upper and lower blazes. (Record, 52 lks.)
A maple, 12" diam., bears S.38°W., 34 lks., Hemlock scribe marks 24S R2W CS BT visible on a partially healed blaze. (Record, fir.)
A root hole, bears N.73°W., 58 lks., with a down maple alongside, 12" diam., with illegible scribe marks on a burnt blaze. (Record, 28 lks.)
and bearing trees mkd. by Tracy
A hemlock, 10" diam., bears N.54°E., 44 lks., with healed blaze.
A hemlock, 27" diam., bears N. 27° W., 46 lks., with scribe marks S R2W CS visible on a partially healed blaze.

Ron Quimby - Crew: Fromdahl & Olsen - 6/2014 - C.S. File 65/82-44

Found - DCSO Brass cap (properly mkd)
18" Hemlock N.54°E., 29.1 ft. good scar.
44" Fir N.85°E., 21.8 ft. good scar.
30" Fir snag S.33°E., 30.4 ft. good scar.
30" Hemlock N.27°W., 30.4 ft.
New BT - 30" Hemlock S.12°W., 9.3 ft. scribed T24S R2W S14 BT
Note - Corner is in the SW corner of old logging approx. 200' NW of the end of skid road.
Compass decl. 15½°E.