

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2898-9)

-----  
Set a basalt stone 18x12x6" 12" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A Fir, 30" dia., bears S.82°E., 15 lks., mkd: ¼ S BT.

A \*, 24" dia., bears N.47°W., 27 lks., mkd: ¼ S BT.

\* No species of tree given on the official fiche per research 3/24/2004 DCSO JC

Douglas Co. Surveyors Office - John Powell - Willie Penley - Aug. 1970 - C.S. File 54/27-226

-----  
Found - 30" now 39" D.Fir S.82°E., 9.9 ft. shows good scar.  
24" now 28" D.Fir N.47°W., 17.8 ft. shows good scar.  
18"x12"x6" stone at ¼ corner mkd: "¼" on west face.

Set - Brass cap at cor. mkd: County Surveyors T24S R2W  
Office 1970 ¼ S11|S12

All BTs ok & tagged.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1533, surveyed May. 1990 - (DCSO records Vol. 50 Page(s) 18999)

-----  
The ¼ sec. cor. of secs. 11 & 12, perpetuated by Powell, in 1970, monumented with an iron post, 1½" diam., firmly set, projecting 10" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S R 2 W

¼ S 11 | S 12

1970

from which the original bearing trees

A fir, 36" dia., bears S.82°E., 15 lks., with healed blaze

A fir, 24" dia., bears N.47°W., 27 lks., with healed blaze