

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2901)

Set a basalt stone 12x7x7" 8" in the ground for ¼ sec. cor. marked ¼ on W face, from which
A fir, 24" dia., bears N.58°W., 33 lks., mkd: ¼ S BT.
A fir, 36" dia., bears N.10°E., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - July 1970 - C.S. File 54/27-233

Found - Orig. corner stone, as called for, in place, & mkd: "¼" on W face.
Orig. 24" now 30" Fir, alive, N.58°W., 21.8 ft., shows good scars, we tag.
Orig. 36" now 40" Fir, alive, N.10°E., 13.9 ft., shows good scars, we tag.
Set - Brass cap at cor. mkd: County Surveyors T24S R2W (Reset old stone alongside) Office 1970 ¼ S 2|S 1
New BT - 16" Hemlock S.34°E., 19.8 ft., mkd: "¼ S1 CS BT"
This corner lies on moderate southerly slope about 620 ft. N of a fork of Rock Creek, course SE