

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2867)

Set post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S. on N. face, from which
A Fir 16" dia., bears N.21°W., 52 lks. dist. mkd. ¼ S BT.
A Fir 18" dia., bears S.29°W., 13 lks. dist. mkd. ¼ S BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13277)

"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon."

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd:

¼ S 36
1951

from which bearing trees marked in 1951

A Fir 20" dia., bears N.35°E., 21 lks. dist. mkd. ¼ S36 BT

A Fir 16" dia., bears N.63°W., 56 lks. dist. mkd. ¼ S36 BT